Mr./Mrs/Ms:					Mod	Model:							Reg.No:				
Invoice/Job no:					_ Odd	Odometer reading:							V.I.N:				
Service type:	Α	В	Α	С	Α	В	Α	С	Α	В	Α	С	Α	В	Α	С	
Months/,000 km:	6/10	12/20	18/30	24/40	30/50	36/60	42/70	48/80	54/90	60/100	66/110	72/120	78/130	84/140	90/150	96/160	



# **RANGE ROVER**

## (ALL MODELS 02 MY ON) **MAINTENANCE CHECK SHEET**

Adjust/Lubricate/Replace - Labour cost included in scheduled time except items marked \*

Check - After the checking procedure, cleaning, adjusting, repairing or replacing is subject to extra labour and material cost.

	Α	В	С	UNDER BONNET				
35.				Check battery condition				
36.			80k	Flush diesel intercooler element				
MAIN SERVICE (UNDER VEHICLE)								
37.				Renew engine oil and filter				
38.				Renew manual gearbox oil				
39.				Check and top up manual gearbox oil				
40.				Renew automatic transmission filter - First 40,000 km only				
41.				Renew automatic transmission oil				
42.				Renew transfer box oil				
43.	[			Check and top up transfer box oil				
44.			160k	Renew front and rear axle oil - First 10,000km only then 160,000km				
45.				Check and top up front and rear axle oil				
46.				Lubricate propeller shaft universal/sliding joints				
47.				Check visually, brake, fuel, clutch pipes, unions, and electrical harnesses for chafing, leaks and corrosion.				
48.				Check for fluid leaks from power steering and suspension systems hydraulic pipes and unions for chafing and corrosion				
49.				Check for fluid leaks from Engine, Gearbox, Transfer box and Axles				
50.				Check exhaust system for leaks , security and damage				
51.	[			Check/tighten steering box, front and rear axle fixings and suspension fixings.				
52.				Check steering rod ball joint fixings and condition of ball joints and dust covers				
53.				Check air suspension pipes and springs for security and damage				
54.				Check shock absorbers/height sensors and harness assembly for leakage and damage				
55.				Check security of towing bracket				
56.				If fault lamp(s) are illuminated, interrogate that system using TestBook and report findings				
57.				Carry out road or roller test (see WARNING over page)				
58.				Endorse service record				
59.				Report any unusual features of vehicle condition and additional work required				
The frequ	ent at	tentior	n may b	listed, are those recommended for vehicles operating under normal driving, road and climatic conditions. More be necessary if the vehicle is subject to stop/start operation, extremes of temperature, dusty conditions, off road g of trailers.				
Servi	ce che	eck co	mpleted	d and service portfolio book endorsed				
				·				
Nan	ne:			Signature: Date:				

A B C VEHICLE INTERIOR		Α	В	С
Note: Petrol models do not require service "A".	(	35.		
2. Check condition and security of seats and seat belts		36. 36.		80k
Check operation of all lamps, horns and warning indicators				
Check operation of front/rear wipers and washers and condition of wiper blades			1	
5. Check operation of handbrake		37. L	ـــــال	
6. Replace alarm handset batteries		38.		
VEHICLE EXTERIOR		39.		
Annual corrosion/cosmetic inspection - Only on vehicles sold after 28/11/98		40.		
		<b>1</b> 1.		H
Branch (after the control of the con		12.		
Parameter size and a supplier and an analysis of the supplier		43. 	1	160k
Charles the standard to the st		14. ∟	1	[100K] 1
		<b>4</b> 5.		·
		46	Щ	
Check tyre pressures, condition and tread depth.	2	<b>1</b> 7. ∟		: لــــــا ¡
LHF RHF RHR LHR Spare	,	18.		
Inspect brake pads for wear, calipers for leaks and discs for condition	-	ю. ш	,	'',
5. Inspect road wheel speed sensor harness for damage	4	19.		
80k Renew fuel filter element (V8) <b>To VIN WA410481</b>	Ę	50.		
7. Renew fuel filter element <b>Every 30,000 km/18 months (Diesel)</b>		51.		
B Drain fuel sedimenter ( <i>Diesel only</i> )		52.		
9. Refit road wheels to original hub position ( Use anti-seize compound on spigot bore )	ŗ	53.		i
D. Visually check intercooler/radiator for external obstructions and fan blades for damage	1	54.		i
1. Check operation and Lubricate door locks, hinges, door checks, bonnet catch & fuel fla	an	55.		i i
2. Check sunroof drain tubes		56.		
UNDER BONNET	Ì	<i>7</i> 0.		1
8 60k 120k Renew anti-freeze	ţ	57. 🖳		
4. 60k 120k Renew brake fluid	Ę	58.		
5. Check cooling, intercooler and heating systems for leaks, hoses and oil pipes for	Ę	59		
security and condition . Top up as required	T	he mair	ntenance	e items li
Renew charcoal canister, check evaporative loss system and fuel filler flap seal (V8)	fr	equent	attentior	n may be
7. 120k Renew spark plugs	dı	iving or	frequer	nt towing o
8. Renew air cleaner element and clean drain hole ( V8 )	S	ervice c	heck co	mpleted a
Renew air cleaner element and clean drain hole ( Diesel )				
0. Renew pollen filters	N	lame:		
Check condition of ancillary driving belt				
2. 100k Renew ancillary driving belt				
Check condition of steering intermediate shaft				
Check/top up brake, PAS and clutch fluid levels and screen washer reservoirs				
· <u> </u>				

10/01 LRL0354ENX(3)

### **WARNING:**

Two wheel roller tests must not be carried out. Four wheel roller tests must be restricted to 5km/h.

#### **IMPORTANT**

#### **OIL CHANGE DIESEL ENGINES**

If the vehicle is operated on fuel with a high sulphur content (over 1%) the oil change intervals must not exceed 10,000 km

#### **VEHICLES FITTED WITH SUPPLEMENTARY RESTRAINT SYSTEMS**

The seatbelt pre-tensioners (where fitted) and air bags must be replaced every TEN YEARS

Side air bags must be replaced every FIFTEEN YEARS

#### IT IS RECOMMENDED THAT:

At 120,000 km or every six years, whichever is the sooner, all hydraulic brake fluid seal and hoses should be renewed.

All working surfaces of the caliper cylinders should be examined and renewed where necessary.

Vehicles used extensively in arduous/off road conditions - check the road wheel speed sensors, brake pads and calipers for abrasive wear at 1500 km intervals

Air suspension vehicles used extensively in arduous/off road conditions will require the compressor inlet and exhaust filters to be replaced at more regular intervals.

When the vehicle is used in dusty or field conditions or deep wading, frequent attention to the air cleaner may be required.

When the vehicle is used in areas where fuel quality is poor, more frequent draining of the fuel filter/sedimentor may be required.

#### **GLOSSARY**

**LUBRICATION SERVICE "A"** = The lubrication service is carried out between main services, the first at 6 months or 10,000 km, whichever occurs first, and then at every subsequent 12 months or 20,000 km. i.e. 30,000 km, 50,000 km etc.

Note: Petrol models do not require service "A".

MAIN SERVICE = The main service is applicable to all vehicles. It is carried out at 12 month or 20,000 km intervals, whichever occurs first.

Main Service "B"is applicable at 12 months/20,000 km, 36 months/60,000 km, 60 months/100,000 km 84 months/140,000 km and so on.

Main Service "C"is applicable at 24 months/40,000 km, 48 months/80,000 km, 72 months/120,000 km, 96 months/160,000 km, and so on. Some items do not need to be carried out at every main service and these items are identified by an indicator in the tick box e.g. 100k (This indicates that this item is only applicable every 60 months/100,000 km)